

PCI
EXPRESS®



 Digigram

Professional multichannel sound cards

PCI Express series of VX sound cards

Boarding pass to a new world

Digigram now offers PCI Express versions of its VX881HR and VX882HR linear sound cards for demanding applications in broadcast such as production, on-air, and logging. Exacting specs, outstanding quality, absolute reliability and total connectivity make this new generation the number one choice for pro audio manufacturers and software vendors. The VX881e and VX882e multichannel sound cards share the same features as the HR series and integrate seamlessly with the same professional audio software.



These sound cards are visiblu ready : get connected to the world of distributed IP audio. A solution based on visiblu®, the Network Audio Operating System by Digigram, takes advantage of their power for low latency wide area network encoding and processing, whether they are located next door or hundreds of miles away.

PCI Express linear sound cards with 4 stereo inputs and 4 stereo outputs:

- VX882e: analog and digital I/Os
- VX881e: digital I/Os
- Up to 24-bit/192 kHz
- Comprehensive set of Windows® drivers: Digigram np, WDM DirectSound (digitally signed by Microsoft®), Wave, ASIO
- High-quality hardware sample rate converters
- Compact design that fits in small PCs
- Optional breakout box

PCI Express series of VX sound cards

VX882e

VX881e

Configuration	
Bus/Format	PCI Express™ X1 (compatible with X1, X2, X4, X8, X12, X16, X32 slots)
Size	167.7 mm X 106.7 mm X 17.1 mm
Digital Signal Processor & RAM	Motorola 56321 at 240 MHz 512 kWords
Operating: temp / humidity (non-condensing)	0°C/+50°C * • 5%/90%
Storage: temp / humidity (non-condensing)	-5°C/+70°C • 0%/95%
Inputs	
Balanced analog line inputs (mono)	8
Maximum input level / impedance	+24 dBu / > 10 kΩ
Sampling frequencies available	Programmable from 8 to 192 kHz
A/D and D/A converter resolution	24 bits
Digital inputs (stereo)	4 AES/EBU with hw Sample Rate Converters, 7.5:1 to 1:8, up to 192 kHz
Programmable input gain	analog and digital
PCM recording (encoding)	8, 16 or 24 bits
Other inputs	AES/EBU Sync (up to 192 kHz), Word clock (up to 96 kHz), LTC, Video
AES11 synchronization	Yes
Outputs	
Analog line outputs (mono)	8 servo-balanced
Maximum output level / impedance	+24 dBu / < 100 Ω
Digital outputs (stereo)	4 AES/EBU, up to 192 kHz
Programmable output gain	analog and digital
Other outputs	Word clock, inter-board sync
Connectors	
External connector	68-pin HD SCSI
Digigram accessories available	XLR breakout cable, 2 RU 19" rack-mount breakout box with Neutrik® connectors
Internal connector	Inter-board sync
Audio performance measured at Fs=48 kHz	
Frequency response (record + play)	20 Hz -20 kHz: 0/-0,2 dB
Dynamic range	Analog In: >104 dB
(A-weighted)	Analog Out: >106 dB
THD + noise 1 kHz at -1 dBfs	Analog In: <-97 dB
	Analog Out: <-96 dB
Channel phase difference: 20/20kHz	0.2° / 2°
Crosstalk (Analog in or out)	1 kHz at 22 dBu: <-100 dB
	15 kHz at 22 dBu: <-85 dB
Development environments and on-board processing	
Supported OS	Windows XP and Windows Vista
Management	np SDK, Wave, ASIO, DirectSound (all: PCM only)
Main on-board processing features (with np SDK)	PCM play, rec, direct monitoring, real-time mixing, level adjustment, panning, cross-fade, punch-in/punch-out, scrubbing, frequency conversions, DigiQMAX 3-band parametric EQ and maximizer

* With two cards installed next to each other, the host computer must be suitably aerated.



Digigram (www.digigram.com) digital audio solutions are key to the success of public address and pro sound installations, as well as broadcast and media production companies worldwide. We develop innovative networked audio devices, computer sound cards, and audio management software.

Digigram Powered solutions are installed in thousands of radio and television stations; corporate and commercial sound installations; and audio recording and video post-production facilities around the globe.

Customers are served from three regional business units: Digigram SA (Digigram Headquarters, Montbonnot, France), Digigram Inc. (Arlington, VA USA), and Digigram Asia (Singapore). Digigram is publicly traded on the Paris stock exchange (Code ISIN: FR 00000 35784).

Digigram SA

(Serving Europe, Africa, Middle East, Latin America)

Parc de Pré Milliet
38330 Montbonnot-FRANCE
Tel: +33 (0)4 76 52 55 01
Fax: +33 (0)4 76 52 53 07
E-mail: sales@digigram.com

Digigram Inc.

(Serving North America)

2101 Wilson Boulevard, Suite 1004,
Arlington, VA 22201-USA
Tel: +1 703 875 9100
Fax: +1 703 875 9161
E-mail: input@digigram.com

Digigram Asia Pte Ltd.

(Serving Asia and Australia/Oceania)

350 Orchard Road
#19-07 Shaw House Singapore
238868-SINGAPORE
Tel: +65 6291 2234 - Fax: +65 6291 3433
E-mail: info_asia@digigram.com

www.digigram.com